

CHARTER TOWNSHIP OF CHESTERFIELD - BUILDING DEPARTMENT

47275 Sugarbush, Chesterfield Township, MI 48047 Phone: (586) 949-0400 Fax: (586) 949-4780

APPLICATION FOR BUILDING PERMIT, ZONING COMPLIANCE

PERMIT AND PLAN EXAMINATION

Authority: P.A. 230 of 1972, as amended Completion: Mandatory to obtain permit Penalty: Permit will not be issued	<h2 style="margin: 0;">Permit #</h2>
--	--------------------------------------

In order to avoid delay all forms must be completely filled out and plans must contain required information.

NOTE: Separate applications must be filled out for electrical, mechanical and plumbing permits.

PROJECT INFORMATION

Job Address	Lot Number	Subdivision
-------------	------------	-------------

PROJECT DESCRIPTION/TYPE OF IMPROVEMENT

Detailed Description of Project <div style="border: 1px solid black; padding: 5px; margin-top: 10px; display: inline-block;"> <h3 style="margin: 0;">Re-Roof (Residential)</h3> </div>	Estimated Cost of Construction \$
---	--

This Section is for new construction only - DIMENSIONS AND DATA

Square Footage - 1st Story _____ 2nd Story _____ Basement _____ Garage _____ TOTAL _____	# of Bedrooms _____ # of Bathrooms Full _____ Half _____ Finishing Basement - Yes/No	Fees: (for office use only) _____ _____ _____ _____ _____
---	---	--

APPLICANT INFORMATION

Name(print)	Address, City, State, Zip		
Email		Phone	
Drivers License Number	Date of Birth	Builders License(if applicable)	Exp date
Company Name(if applicable)			

I hereby certify that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent, and we agree to conform to all applicable laws of the Charter Township of Chesterfield and the State of Michigan. All information submitted on this application is accurate to the best of my knowledge.

Section 23a of the state construction code act 1972, 1972 PA 230, MCL 125.1523A, prohibits a person from conspiring to circumvent the licensing requirements of this state relating to persons who are to perform work on a residential building or residential structure. Violators of section 23a are subject to civil fines.

HOMEOWNER AFFIDAVIT

I hereby certify the building work described on this permit application shall be installed by myself in my own home in which I am living or about to occupy. All work shall be installed in accordance with the Building Code and shall not be enclosed, covered, used, or put into operation until it has been inspected and approved by the Building Inspector. I will cooperate with the Building Inspector and resume responsibility to arrange for necessary inspections.
--

BOND HOLDER INFORMATION

Bond Holder(this who the bond check will be refunded to)
--

Address, city, state, zip

SIGNATURE Signature of Applicant - Must be signed by Homeowner or Contractor (Homeowner Signature indicates compliance with Section VI. Homeowner Affidavit)	Date
---	------

Re-Roof Permit Application
Residential only

When applying for a permit for a re-roof, you will need the following:

- 1. Building application**
- 2. Drivers license and/or Builders license**
- 3. Copy of general liability and workman's comp insurance certificate
(Builder only)**
- 4. Copy of the plan review signed and dated**

***All are required for every application, any copies needed will be charged \$1.00 per copy**

***The cost for re-roof permit is \$200.00 (The registration fee is an additional \$20.00, if you are a builder)**

****ADDITIONAL FEES MAY BE ADDED IF WORK STARTED PRIOR TO PERMIT BEING PULLED****

****This form is for Residential only**

ROOFING MATERIAL CHECKLIST

ADDRESS_____

- UNDERLAYMENTS:**
- ICE & WATER 3'___ 4.5'___ 6'___ OTHER_____**

- 15# FELT PAPER___ 30# FELT PAPER___ SYNTHETIC PAPER___

- **EXHAUST VENTILATION:**

- RIDGE___ LENGTH USED_____

- CANS___ NUMBER USED_____

- GABLE___ NUMBER AND SIZE_____

- POWER VENT___ NUMBER AND SIZE_____

- **INTAKE VENTILATION:**

- 4" X 16" SOFFIT VENTS___ QUANTITY_____

- 8" X 16" SOFFIT VENTS___ QUANTITY_____

- PERFORATED SOFFIT PANELS___ QUANTITY_____

- STARTER OR EDGE VENT___ QUANTITY_____

COMPANY NAME_____

PERMITEE_____

DATE_____ PHONE NUMBER_____

**2009 MICHIGAN
CODE
PLAN REVIEW**

DATE_____ RESIDENTIAL

JURISDICTION _____ CHESTERFIELD TOWNSHIP
(City, County, Township, etc.)

BUILDING _____
(STREET ADDRESS)

BUILDING DESCRIPTION _____ REQUIREMENTS FOR ROOF COVERINGS

Numerals indicated in parenthesis are applicable code sections of the 2009 International Building Code. The plan review accomplished as indicated in this record is limited to those code sections specifically identified herein. This record references commonly applicable code sections. It does not reference all code provisions which may be applicable to specific buildings. This record is designed to be used only by those who are knowledgeable and capable of exercising competent judgement in evaluating construction documents for code compliance.

CORRECTION LIST

1. 15lb. underlayment is required under asphalt shingles. Underlayment shall be applied shingle fashion, parallel to and starting from the eave and lapped 2", fastened sufficiently to hold in place. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. An ice barrier that consists of at least two layers of underlayment cemented together or a self-adhering polymer modified bitumen sheet shall be used in lieu of normal underlayment and extend from the lowest edge of all roof surfaces to a point at least 24" inside the exterior wall line of the building. Sections R905, R905.101, R 905.1.2
2. Fasteners for asphalt shingles shall be galvanized steel, stainless steel, aluminum or copper roofing nails, minimum 12 gage [0.105 inch (2.67mm)] shank with a minimum 3/8" (9.5mm) diameter head. ASTM F 1667, of a length to penetrate through the roofing materials and a minimum of 3/4" (19.1mm) into the roof sheathing. Section R905.2.5
3. Asphalt shingles shall have the minimum number of fasteners required by the manufacturer. For normal application, asphalt shingles shall be secured to the roof with not less than four fasteners per strip shingle of two fasteners per individual shingle. Section R905.2.6
4. Base and cap flashing shall be installed in accordance with manufacturer's installation instructions. Section R905.2.8.1
5. Valley linings shall be installed in accordance with manufacturer's installation instructions. Section R903.2.2
6. A cricket or saddle shall be installed on the ridge side of any chimney greater than 30" (762mm) wide. Cricket or saddle coverings shall be sheet metal or of the same material as the roof covering. Section R905.2.8.3
7. Flashing against a vertical sidewall shall be by the step flashing method. Section R905.2.8.3
8. Flashing against a vertical front wall, as well as soil stack, vent pipe and chimney flashing, shall be applied according to asphalt shingle manufacturer's printed instructions. Section R905.2.8.4
9. The total net free ventilating area shall not be less than 1 sq ft to 150 sq ft of the area of the space ventilated. Section R806.2
10. Where eave or cornice vents are installed, insulation shall not block the free flow of air. A minimum of a 1" (24.4mm) space shall be provided between the insulation and the roof sheathing at the location of the vent. Section R806.3
11. For roof slopes under four units vertical in 12 units horizontal underlayment shall be a minimum of two layers underlayment applied as follows (1) Starting at the eave a 19 inch strip of underlayment shall be applied parallel with the eave and fasten sufficiently in place. (2) Starting at the eave 36 inch wide strips of underlayment felt shall be applied overlapping successive sheets 19 inches and fastened sufficiently in place. Table R905.1.1(2)1
12. Roof and ceiling construction shall be capable of supporting all loads imposed according to section R 301 and of transmitting the resulting loads to the supporting structural elements. Section R 801.2
13. New Roof coverings shall not be installed without first removing existing roof coverings where there are 2 or more applications of any type of roof coverings. Section 908.2.1.1
14. The Builder is to see that all litter and discarded building products shall be placed in authorized private receptacles in such a manner as to prevent it from being carried or deposited by the elements upon any street or upon private property. Sections 3302.2, 3306.1, and 3306.8
15. A drip edge shall be provided at eaves and rake edges of shingle roofs. Sections 905.2.8.5

I have read and agree with the above.

X _____ Date _____

2009 MICHIGAN	DATE	RESIDENTIAL
----------------------	-------------	--------------------

**CODE
PLAN REVIEW**

JURISDICTION CHESTERFIELD TOWNSHIP

(City, County, Township, etc.)

BUILDING _____
(STREET ADDRESS)

BUILDING DESCRIPTION REQUIREMENTS FOR ROOF COVERINGS

Numerals indicated in parenthesis are applicable code sections of the 2009 International Building Code. The plan review accomplished as indicated in this record is limited to those code sections specifically identified herein. This record references commonly applicable code sections. It does not reference all code provisions which may be applicable to specific buildings. This record is designed to be used only by those who are knowledgeable and capable of exercising competent judgement in evaluating construction documents for code compliance.

CORRECTION LIST

1. 15lb. underlayment is required under asphalt shingles. Underlayment shall be applied shingle fashion, parallel to and starting from the eave and lapped 2", fastened sufficiently to hold in place. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. An ice barrier that consists of at least two layers of underlayment cemented together or a self-adhering polymer modified bitumen sheet shall be used in lieu of normal underlayment and extend from the lowest edge of all roof surfaces to a point at least 24" inside the exterior wall line of the building. Sections R905, R905.101, R 905.1.2
2. Fasteners for asphalt shingles shall be galvanized steel, stainless steel, aluminum or copper roofing nails, minimum 12 gage [0.105 inch (2.67mm)] shank with a minimum 3/8" (9.5mm) diameter head. ASTM F 1667, of a length to penetrate through the roofing materials and a minimum of 3/4" (19.1mm) into the roof sheathing. Section R905.2.5
3. Asphalt shingles shall have the minimum number of fasteners required by the manufacturer. For normal application, asphalt shingles shall be secured to the roof with not less than four fasteners per strip shingle of two fasteners per individual shingle. Section R905.2.6
4. Base and cap flashing shall be installed in accordance with manufacturer's installation instructions. Section R905.2.8.1
5. Valley linings shall be installed in accordance with manufacturer's installation instructions. Section R903.2.2
6. A cricket or saddle shall be installed on the ridge side of any chimney greater than 30" (762mm) wide. Cricket or saddle coverings shall be sheet metal or of the same material as the roof covering. Section R905.2.8.3
7. Flashing against a vertical sidewall shall be by the step flashing method. Section R905.2.8.3
8. Flashing against a vertical front wall, as well as soil stack, vent pipe and chimney flashing, shall be applied according to asphalt shingle manufacturer's printed instructions. Section R905.2.8.4
9. The total net free ventilating area shall not be less than 1 sq ft to 150 sq ft of the area of the space ventilated. Section R806.2
10. Where eave or cornice vents are installed, insulation shall not block the free flow of air. A minimum of a 1" (24.4mm) space shall be provided between the insulation and the roof sheathing at the location of the vent. Section R806.3
11. For roof slopes under four units vertical in 12 units horizontal underlayment shall be a minimum of two layers underlayment applied as follows (1) Starting at the eave a 19 inch strip of underlayment shall be applied parallel with the eave and fasten sufficiently in place. (2) Starting at the eave 36 inch wide strips of underlayment felt shall be applied overlapping successive sheets 19 inches and fastened sufficiently in place. Table R905.1.1(2)1
12. Roof and ceiling construction shall be capable of supporting all loads imposed according to section R 301 and of transmitting the resulting loads to the supporting structural elements. Section R 801.2
13. New Roof coverings shall not be installed without first removing existing roof coverings where there are 2 or more applications of any type of roof coverings. Section 908.2.1.1

14. The Builder is to see that all litter and discarded building products shall be placed in authorized private receptacles in such a manner as to prevent it from being carried or deposited by the elements upon any street or upon private property. Sections 3302.2, 3306.1, and 3306.8

15. A drip edge shall be provided at eaves and rake edges of shingle roofs. Sections 905.2.8.5

I have read and agree with the above.

X _____ Date _____